

Height Safety Lifting Lashing

DATA SHEET

3053 - K4 WW Waterworks Lanyard

DESCRIPTION

Energy absorbing lanyard 1.8m with stainless steel triple action karabiners.

MATERIALS

- 30kN 44mm Polyester Webbing
- Tear Webbing Activated Between 2 & 6 kN
- High Strength Stainless Steel Triple Action karabiners with captive bar

TESTING

- 100% visual inspection
- Hooks 100% proof tested

FEATURES

- AS/NZ 1891.1 Certified
- Lightweight
- Made in Australia
- Individually serial numbered
- Weight 95g
- Fitted with back up strap
- Clear shrink wrap for ease of inspection
- Stitch patterns easily visible
- Maximum user weight 100kg
- Corrosion resistant attachment fittings

FALL CLEARANCE ALLOWANCES

Length of lanyard = 1800mm Height of operator = 1800mm Residual clearance = 1000mm


Total = 4600mm plus the following values
Fall Distance Energy Absorber Extension

600mm 300mm 1000mm 500mm 1500mm 600mm

2000mm 900mm

* Calculated from the start position of the lanyard







APPLICATIONS

Suitable for all general fall arrest applications particularly in corrosive environments Including roof work, maintenance, construction, offshore, oils & gas, petrochemical and confined space entry.

COMPATIBILITY

Compatible with all SpanSet fall arrest harnesses.

SPANSET ACCREDITATIONS



Certified manufacturer to AS/NZS 1891.1 "Fall Arrest Equipment"
Certified manufacturer to AS/NZS 1353.1 "Flat Synthetic Webbing Slings"
Certified manufacturer to AS/NZS 4497.1 "Round Slings —Synthetic Fibre"
Certified testing laboratory for all of the above



Certified to ISO 9001 Quality Systems



Certified to NATA National Association of Testing Authorities



Registered Training Organisation Founding member of FPMA Fall Protection Manufacturers Association Member Hire Industry Association of Australia

TRAINING COURSES AVAILABLE



- WORK SAFELY AT HEIGHTS: MNMG237A
- WORK SAFELY ON ROOFS: CPCPCM2105A
- WORK SAFELY AT HEIGHTS: CPCCCM1006A
- COMPETENT PERSON PRACTICAL INSPECTION & RECORD KEEPING: MEM15004B
- TOWER & POLE RESCUE: PUAOHS001B, PUASAR001A, PUASAR004A
- VERTICAL RESCUE: PUAOHS001B, PUASAR001A, PUASAR004A
- ENTER CONFINED SPACE: MSAPMPER205B, MSAPMPER200B,
- OPERATE BREATHING APPARATUS: MSAPMOHS216A
- CONFINED SPACE VERTICAL RESCUE: PUAOHS001B, PUASAR001A, PUASAR004A

OTHER PRODUCTS AVAILABLE

- ABS ratchet systems
- Supra Plus Round Slings
- Secutex edge protection
- Web Dog Chain tensioners
- Round Slings to 100 tonne
- Flat Slings To 20 tonne

Made in Australia by SpanSet Australia Ltd

13 Pullman Place, Emu Plains NSW 2750 Phone: 02 4735 3955 Fax: 02 4735 3630

Copyright © 2010 Spanset Australia Ltd.

www.spanset.com.au

International Website: www.spanset.com